

DUPLOGEL INTRODUCIR

FOR THE INSTALLATION OF (NEW) CABLES

It facilitates the insertion of the cables in underground installations.

- Thick, almost gelatinous, water-based lubricant gel.
- It eliminates up to 80% of friction between cables and pipe walls and other cables already installed.
- No glue effect. No clogged cables.
- It evaporates leaving no waste.
- Non-toxic, inert, non-flammable.
- It does not harm the skin. Non-irritant.
- Working temperature: -10°C to +50°C



INSTRUCTIONS FOR USE:

From the outside, apply lubricant onto a sponge and wipe the entire cable with it, beginning at one end and covering the entire length of the cable to be installed.

PRODUCT	UNITS/BOX	REF.	PRICE €/u.
DUPLOGEL INTRODUCIR Lubricant Gel 500 cc	12	4.6015.000	6.50
DUPLOGEL INTRODUCIR Lubricant Gel 1000 cc	12	4.6016.000	10.50
DUPLOGEL INTRODUCIR Lubricant Gel 5000 cc	1	4.6017.000	45.00
DUPLOGEL INTRODUCIR Lubricant Gel 25 LITRES (PAIL)	1	4.6019.000	190.00

CABLE LUBRICANTS

AEROSOL LUBRICANT FOAM

FOR THE INSTALLATION OF (NEW) CABLES

It lubricates the pipe to ease the entry of new cables.

- It is applied inside the pipe before the cables are inserted.
- Greater contact between the lubricating foam and the cable.
- The cables drag the lubricating foam all along the pipe, thus facilitating foam penetration.
- It eliminates up to 80% of friction between cables and pipe walls and other cables already installed.
- Clean, quick and practical. No spilling.
- No glue effect. No clogged cables.
- It evaporates leaving no waste.
- Biodegradable. Non-toxic, harmless.
- It does not harm the skin. Non-irritant.
- The product is non-flammable (only the propellant gases are flammable).
- Working temperature: -0°C to +50°C.



INSTRUCTIONS FOR USE:

Shake before use.

Fit the nozzle into the valve and insert it into the pipe, keeping the aerosol can upright.

Press the spray for a few seconds and the lubricant foam will penetrate into the pipe directly for a couple of metres, depending on the amount applied. Then push the cable through.

PRODUCT	UNITS/BOX	REF.	PRICE €/u.
Aerosol Lubricant Foam 400 ml	12	4.6030.000	8.20
Extra-long NOZZLE KIT for Lubricant Foam	1	4.6030.001	3.00

DUPLOGEL EXTRAER

FOR THE REMOVAL OF (OLD) CABLES

It eases the removal of cables already installed in trunking and pipes.

- Highly fluid water-based lubricant.
- It reduces friction and makes it possible to release trapped cables inside the pipe.
- No glue effect.
- It evaporates leaving no waste.
- Non-toxic, inert, non-flammable.
- It does not harm the skin. Non-irritant.
- Working temperature: -4°C to +60°C.



INSTRUCTIONS FOR USE:

Pour enough product to cover the entire cable route in through the top of the trunking.

If it does not flow directly from top to bottom and along bends or elbows, blow in air to facilitate distribution.

Allow the product to act for a few minutes and then pull the cable out.

PRODUCT	UNITS/BOX	REF.	PRICE €/u.
DUPLOGEL EXTRAER Lubricant Gel 500 cc	12	4.6020.000	6.50
DUPLOGEL EXTRAER Lubricant Gel 25 LITRES	1	4.6025.000	190.00